

SISSONS PAINTS (THAILAND) LTD.

Office: 91/2 moo 3, Suwintawong Rd., Minburi, Bangkok 10510

Tel: 0-2517-1146, 0-2918-6760-1 Fax: 0-2517-2137

SISCOFLOOR 105

EPOXY CONCRETE SEALER

PRODUCT DESCRIPTION	A two component, Epoxy concrete primer for new concrete. It is good penetrate into concrete and promote and enhance adhesion of subsequent coatings.					
SPECIFIC PROPERTIES	Excellent intercoat adhesion properties. Excellent water and alkali resistance performance. Can be Cured on wet concrete or high humidity concrete.					
PHYSICAL DATA APPLICATION DATA	Solids (% by volume) Dry Film Thickness Wet Film Thickness Flash Point Theoretical Coverage Colours Gloss Application method		. 50% 40-50. microns 80-100.microns > 90 °C 38-47 m²/USG/time Clear Gloss Air spray, Brush, roller			
	Temperature minimum Humidity Maximum For Air Spray Pressure Viscosity Dilution Mixing Ratio Drying Time 0 °C 85% R.H. 2.8-3.0 kg/cm² 2.8-3.0 kg/cm² 12-17 sec.(Ford cup no.4) Not require 1 Base : 1 Hardener (by weight)					Pot
	Temperature	rouch bry	liara Dry	Minimum	Maximum	Life
	25 °c	6 Hrs	24 Hrs	10 Hrs		12 Hrs
	30 °c	4 Hrs	12 Hrs	6 Hrs		8 Hrs
	35 °c	2 Hrs	8 Hrs	3 Hrs		6 Hrs
ADDITIONAL INFORMATION	Cleaning Solvent Thinner No.9 Packaging Two pack product 1 and 5 USG Preferable Preceding Coats Preferable Subsequent Coats Siscoguard finish, Siscoguard finish HB, Siscothane AC etc.					
SAFETY PRECAUTIONS	Ensure that there is adequate ventilation in the area where the product is being applied. Do not breath vapour or spray. In case of touch skin, wash skin thoroughly soap and water. In case of accidental eyes splashes, flush eyes with warm water immediately and obtain medical advice.					
DISCLAIMER	The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.					