



SISSONS PAINTS (THAILAND) LTD.

Office : 91/2 moo 3, Suwintawong Rd., Minburi, Bangkok 10510

Tel : 0-2517-1146, 0-2918-6760-1 Fax : 0-2517-2137

SISCOLIC ACRYLIC FLOORING FINISH

FLOORING ACRYLIC COATING

PRODUCT DESCRIPTION	A gloss finish base on acrylic resin for used on concrete flooring. . It's small particle size to penetrate into concrete that promoted adhesion properties.					
SPECIFIC PROPERTIES	Fast Dry finish/primer Excellent adhesion. Excellent gloss and colour retention. Can be use both primer and topcoat.					
PHYSICAL DATA	Solids (% by volume)	..50...%				
	Dry Film Thickness	30 .microns				
	Wet Film Thickness	60..microns				
	Flash Point	32 °C				
	Theoretical Coverage	30 m ² /USG/time				
	Colours	White, as specified				
	Gloss	Gloss				
APPLICATION DATA	Application method	Brush, roller				
	Temperature minimum	0 °C				
	Humidity Maximum	85% R. H.				
	Dilution	Thinner no.10				
	Drying Time					
		Surface Temperature	Touch Dry	Hard Dry	Over coating Interval	Pot Life
					Minimum	Maximum
		25 °C	15 Mins	2 Hrs	3 Hrs	--
		30 °C	10 Mins	1 Hrs	2 Hrs	--
		35 °C	5 Mins	30 Mins	1 Hrs	--
ADDITIONAL INFORMATION	Cleaning Solvent	Thinner No.10				
	Packaging	One pack product 1 and 5 USG				
	Preferable Preceding Coats	-				
	Preferable Subsequent Coats	-				
SAFETY PRECAUTIONS	Ensure that there is adequate ventilation in the area where the product is being applied. Do not breath vapour or spray. In case of touch skin, wash skin thoroughly soap and water. In case of accidental eyes splashes, flush eyes with warm water immediately and obtain medical advice.					
DISCLAIMER	The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.					