

PRODUCT DESCRIPTION	A high-build quick dry alkyd primer containing iron oxide as rust-preventing pigment.																																
SPECIFIC PROPERTIES	High effective rust – preventing primer Quick drying properties Excellent adhesion																																
PHYSICAL DATA	Solids (% by wt.) > 50.....% Fineness < 50 microns Viscosity 25°C 75-90 microns Touch Dry < 3 Hrs Hard Dry < 8 Hrs Specific Gravity > 1.45 Adhesion > 85% Colours Reddish Brown																																
SOURCE OF MATERIALS	<table><thead><tr><th>TYPE</th><th>BRAND</th><th>COUNTRY</th></tr></thead><tbody><tr><td>1. ALKYD RESIN</td><td>BECKOSOL</td><td>LOCAL</td></tr><tr><td>2. PIGMENT</td><td>ZAR</td><td>GERMANY</td></tr><tr><td>3. ADDITIVE</td><td></td><td></td></tr><tr><td>DISPERSING AGENT</td><td>NUODEX</td><td>U.S.A</td></tr><tr><td></td><td>COGNIS</td><td>LOCAL</td></tr><tr><td>ANTI-SETTLING</td><td>ROCKWOOD</td><td>U.S.A</td></tr><tr><td>ANTI-SKINNING</td><td>SERVO</td><td>ENGLAND</td></tr><tr><td>DRIER</td><td>TROY</td><td>U.S.A</td></tr><tr><td>4. WHITE SPIRIT</td><td>SHELL</td><td>LOCAL</td></tr></tbody></table>			TYPE	BRAND	COUNTRY	1. ALKYD RESIN	BECKOSOL	LOCAL	2. PIGMENT	ZAR	GERMANY	3. ADDITIVE			DISPERSING AGENT	NUODEX	U.S.A		COGNIS	LOCAL	ANTI-SETTLING	ROCKWOOD	U.S.A	ANTI-SKINNING	SERVO	ENGLAND	DRIER	TROY	U.S.A	4. WHITE SPIRIT	SHELL	LOCAL
TYPE	BRAND	COUNTRY																															
1. ALKYD RESIN	BECKOSOL	LOCAL																															
2. PIGMENT	ZAR	GERMANY																															
3. ADDITIVE																																	
DISPERSING AGENT	NUODEX	U.S.A																															
	COGNIS	LOCAL																															
ANTI-SETTLING	ROCKWOOD	U.S.A																															
ANTI-SKINNING	SERVO	ENGLAND																															
DRIER	TROY	U.S.A																															
4. WHITE SPIRIT	SHELL	LOCAL																															
ADDITIONAL INFORMATION	Cleaning Solvent Thinner No.1 Packaging one pack product 1 and 5 USG Preferable Preceding Coats - Preferable Subsequent Coats Tungolac Enamel, and other alkyd resin based paints																																
SAFETY PRECAUTIONS	Ensure that there is adequate ventilation in the area where the product is being applied. Do not breath vapour or spray. In case of touch skin, wash skin thoroughly soap and water. In case of accidental eyes splashes, flush eyes with warm water immediately and obtain medical advice.																																
DISCLAIMER	The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.																																